

Listed by UL



W32ES-1



HWS-4

Requires a scale for free-standing unit

MODEL NO.	W32ES-1	W32C-5	W32-6	HWS-4-C
Usage	Semi-Automatic	Free-Standing	Free-Standing	Free-Standing
Frame	Stainless Steel	Aluminum	Aluminum	Stainless Steel
Wrapping Surface	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Sealing Element	8" x 15" On-Demand Hotplate	8" x 15" Hotplate	N/A	6" x 15" Hotplate
Cutting Element	Low Temperature Heated Rod	Low Temperature Heated Rod	Low Temperature Film Cut Off System	Low Temperature Stainless Steel Heated Rod
Dimensions Width x Length	25" x 24"	22½" x 26"	12½" x 25"	52¼" Wide x 28" Deep Includes Shelves 27" Wide Without Shelves
Height	33" to 39" Adjustable	37" to 39½"	37" to 39½" Adjustable	36¼"
Capacity	2 Rolls 8" to 20" – 3" Core Plug, Maximum OD 9½"		2 Rolls 8" to 18" – 3" Core Plug, Maximum OD 9½"	2 Rolls, Maximum OD 3" Core Plug, 8" to 20" Wide
Electrical	120/60/1 1 Amp	120/60/1 8.5 Amp	100-120/60/1 1 Amp	120/60/1 8.5 Amp
Shipping Weight	90 lbs.	60 lbs.	50 lbs.	90 lbs.

Optional Equipment for W32ES-1 Only

- + **ES-SHELF-LT** – Left side shelf for left to right configuration
- + **ES-SHELF-RT** – Right side shelf for right to left configuration

NOTE: HWS-4 wrap station is available in an Energy Smart version

- **HWS-4-ES** – Energy Smart Hand Wrap Station